Standard Hollow Tine - .750MT x 4.750L x .510OD

R59-3680

Details

Designed to remove a soil core, R&R Standard Hollow Tines are constructed from case hardened tubular steel and are the most economical tines available. Case hardening hardens the inner and outer surfaces of the tine wall to over RC55 for added wear.

Replaces

R&R Products	R59-9760, R66-9140, R94-3419
Toro	59-9760, 66-9140, 94-3419

Specifications

Manufacturer	R&R Products
A - Tine Type	Standard Hollow
B - Tine Mounting Dia.	.750 in (19mm)
C - Tine Length	4.75 in (121mm)
D - Tine Tip Outside (Hole) Dia.	.510 in (12.9mm)
E - Tine Tip Inside (Core) Dia.	.400 in (10.2mm)
F - Tine Wall Thickness	.049 in (1.2mm)

Fits Models

Toro Fairway Aerator
Toro Greens Aerator
Toro ProCore 1298
Toro ProCore 440
Toro ProCore 648
Toro ProCore 660
Toro ProCore 864
Toro ProCore 880

R&R Products Inc
3334 E Milber St Tucson, 85714
800-528-3446
https://www.rrproducts.com/

Standard Hollow Tine - .750MT x 4.750L x .510OD

R59-3680

Toro ProCore 648s

R&R Products Inc
3334 E Milber St Tucson, 85714
800-528-3446
https://www.rrproducts.com/