



Standard Hollow Tine - .750MT x 4.750L x .475OD R59-3690



Details

Designed to remove a soil core, R&R Standard Hollow Tines are constructed from case hardened tubular steel and are the most economical tines available. Case hardening hardens the inner and outer surfaces of the tine wall to over RC55 for added wear.

Replaces

John Deere	TCU17449
R&R Products	R100-3633, R523421, RMT2964, RTCU17449
Toro	59-3690

Specifications

Manufacturer	R&R Products
A - Tine Type	Standard Hollow
B - Tine Mounting Dia.	.750 in (19mm)
C - Tine Length	4.75 in (121mm)
D - Tine Tip Outside (Hole) Dia.	.475 in (12.1mm)
E - Tine Tip Inside (Core) Dia.	.330 in (8.4mm)
F - Tine Wall Thickness	.049 in (1.2mm)
Savings	Volume Buy

Fits Models

John Deere Aercore 1000
John Deere Aercore 1500
John Deere Aercore 2000
John Deere Aercore 800
Ryan GA30
Toro Fairway Aerator

R&R Products Inc

3334 E Milber St Tucson, 85714
800-528-3446

<https://www.rrproducts.com/>



Standard Hollow Tine - .750MT x 4.750L
x .475OD
R59-3690



Toro Greens Aerator
Toro ProCore 1298
Toro ProCore 440
Toro ProCore 648
Toro ProCore 660
Toro ProCore 864
Toro ProCore 880
Toro ProCore 648s

R&R Products Inc

3334 E Milber St Tucson, 85714
800-528-3446

<https://www.rrproducts.com/>