



Alloy Hollow Side-Eject Tine - .750MT x 6.500L x .570OD R108-9167



Details

Manufactured from special high-carbon alloy tubular steel with a precision machined slot in the side wall to allow for more efficient core removal in heavy soils. R&R's unique method of machining maintains the maximum side wall height for strength to avoid bending. These tines are through hardened to RC45-48 to create a much tougher and more wear-resistant tine.

Replaces

Toro 108-9167

Specifications

| | |
|----------------------------------|-------------------------|
| Manufacturer | R&R Products |
| A - Tine Type | Alloy Hollow Side-Eject |
| B - Tine Mounting Dia. | .750 in (19mm) |
| C - Tine Length | 6.5 in (165mm) |
| D - Tine Tip Outside (Hole) Dia. | .570 in (14.5mm) |
| E - Tine Tip Inside (Core) Dia. | .400 in (10.2mm) |
| F - Tine Wall Thickness | .058 in (1.5mm) |
| Savings | Volume Buy |

Fits Models

Toro ProCore 1298
Toro ProCore 440
Toro ProCore 648
Toro ProCore 660
Toro ProCore 864
Toro ProCore 880
Toro ProCore 648s

R&R Products Inc

3334 E Milber St Tucson, 85714
800-528-3446

<https://www.rrproducts.com/>