

D50 1in Full Circle Rotor - w/Check Valve Acme RGWD50C25A







R&R Products Inc

3334 E Milber St Tucson, 85714 800-528-3446 https://www.rrproducts.com/

Details

A full 4-inch pop-up clears tall turfgrass for even coverage. Stainless-steel riser resists damage and vandalism. Special design eliminates blow-by and reduces pressure loss to improve system performance. Dual-direction flushing protects internals from debris and ensures positive popup/down. Radius can be adjusted up to 25 percent for best coverage. Quick lock design allows internals to be serviced from the rotor's top. Range: 53'-74'.

- A full 4-inch pop-up clears tall turfgrass for even coverage.
- Rolled-over flange keeps turfgrass clear of riser and nozzle.
- Stainless-steel riser resists damage and vandalism.
- Tough, commercial-grade plastic case stands up to punishment.
- Special design eliminates blow-by and reduces pressure loss to improve system performance.
- Dual-direction flushing protects internals from debris and ensures positive pop-up/down.
- Uniform coverage with square or triangular spacing.
- Full-circle and adjustable patterns for maximum flexibility.
- Easy arc adjustment in the field without any tools.
- Nozzle kit offers fully interchangeable nozzles and is included with each rotor.
- Unique manual On/Off control for hydraulic rotors.
- Heavy-duty spring assures positive retraction.
- Radius can be adjusted up to 25 percent for best coverage.
- Compact cartridge design allows for quick and easy repair.
- Quick lock design allows internals to be



D50 1in Full Circle Rotor - w/Check Valve Acme

RGWD50C25A



serviced from the rotor s top.

Specifications	
Manufacturer Weathermatic	
Manufacturer's D50C25A	
Model No	
Body Height 9.75 in	
Exposed Cap 6.5 in	
Diameter	
Inlet Size 1 in	
Maximum Pressure 100 psi	
Minimum Pressure 40 psi	
Pop-up Height 4 in	
Spinkler Flow 11.0 - 31.3 gpr	n
Sprinkler Operating 50 - 80 psi Range	
Thread Type ACME	

R&R Products Inc

3334 E Milber St Tucson, 85714 800-528-3446 https://www.rrproducts.com/