



Alloy Machined Side-Eject Tine - .750MT x 4.750L x .550OD R201524



Details

Alloy Machined Side-Eject tines remove a soil core which quickly exits the side of the tine through a precision machined slot. This slot is designed to avoid "plugging" that can occur using hollow tubular tines (especially the smaller diameters) in heavy soil conditions. R&R manufactures a wide selection of these side-eject tines machined from special high-carbon alloy steel solid bar and heat treated to RC45-48 in our own heat treating facility. Very popular for the multiple tine holders which fit all greens aerators.

Specifications

| | |
|----------------------------------|---------------------------|
| Manufacturer | R&R Products |
| A - Tine Type | Alloy Machined Side-Eject |
| B - Tine Mounting Dia. | .750 in (19mm) |
| C - Tine Length | 4.75 in (121mm) |
| D - Tine Tip Outside (Hole) Dia. | .550 in (13.9mm) |
| E - Tine Tip Inside (Core) Dia. | .400 in (10.2mm) |
| F - Tine Wall Thickness | .062 in (1.6mm) |

Fits Models

Jacobsen GA-24
Ryan Greensaire II
Toro Greens Aerator

R&R Products Inc

3334 E Milber St Tucson, 85714
800-528-3446

<https://www.rrproducts.com/>