



Alloy Machined Side-Eject Tine - .750MT x 5.500L x .650OD R201537



Details

Alloy Machined Side-Eject tines remove a soil core which quickly exits the side of the tine through a precision machined slot. This slot is designed to avoid "plugging" that can occur using hollow tubular tines (especially the smaller diameters) in heavy soil conditions. R&R manufactures a wide selection of these side-eject tines machined from special high-carbon alloy steel solid bar and heat treated to RC45-48 in our own heat treating facility. Very popular for the multiple tine holders which fit all greens aerators.

Specifications

| | |
|----------------------------------|---------------------------|
| Manufacturer | R&R Products |
| A - Tine Type | Alloy Machined Side-Eject |
| B - Tine Mounting Dia. | .750 in (19mm) |
| C - Tine Length | 5.500 in (140mm) |
| D - Tine Tip Outside (Hole) Dia. | .650 in (16.5mm) |
| E - Tine Tip Inside (Core) Dia. | .500 in (12.7mm) |
| F - Tine Wall Thickness | .065 in (1.7mm) |

Fits Models

John Deere Aercore 1000
John Deere Aercore 1500
John Deere Aercore 2000
John Deere Aercore 800
Ryan GA30
Toro ProCore 1298
Toro ProCore 440
Toro ProCore 648

R&R Products Inc

3334 E Milber St Tucson, 85714
800-528-3446

<https://www.rrproducts.com/>



**Alloy Machined Side-Eject Tine - .750MT
x 5.500L x .650OD**
R201537



Toro ProCore 660
Toro ProCore 864
Toro ProCore 880
Toro ProCore 648s

R&R Products Inc

3334 E Milber St Tucson, 85714
800-528-3446

<https://www.rrproducts.com/>