



# Alloy Machined Side-Eject Tine - .750MT x 5.500L x .550OD R201536



## Details

Alloy Machined Side-Eject tines remove a soil core which quickly exits the side of the tine through a precision machined slot. This slot is designed to avoid "plugging" that can occur using hollow tubular tines (especially the smaller diameters) in heavy soil conditions. R&R manufactures a wide selection of these side-eject tines machined from special high-carbon alloy steel solid bar and heat treated to RC45-48 in our own heat treating facility. Very popular for the multiple tine holders which fit all greens aerators.

## Specifications

Manufacturer	R&R Products
A - Tine Type	Alloy Machined Side-Eject
B - Tine Mounting Dia.	.750 in (19mm)
C - Tine Length	5.500 in (140mm)
D - Tine Tip Outside (Hole) Dia.	.550 in (13.9mm)
E - Tine Tip Inside (Core) Dia.	.400 in (10.2mm)
F - Tine Wall Thickness	.065 in (1.7mm)

## Fits Models

John Deere Aercore 1000  
John Deere Aercore 1500  
John Deere Aercore 2000  
John Deere Aercore 800  
Ryan GA30  
Toro ProCore 1298  
Toro ProCore 440  
Toro ProCore 648

## R&R Products Inc

3334 E Milber St Tucson, 85714  
800-528-3446

<https://www.rrproducts.com/>



**Alloy Machined Side-Eject Tine - .750MT  
x 5.500L x .550OD**  
R201536



Toro ProCore 660  
Toro ProCore 864  
Toro ProCore 880  
Toro ProCore 648s

**R&R Products Inc**

3334 E Milber St Tucson, 85714  
800-528-3446

**<https://www.rrproducts.com/>**