



Spoton Spray Tip Pressure Tester

RSC28040



Details

Accurately check nozzle pressure between the nozzle and nozzle body, verify accuracy of sprayer pressure sensor or gauge and find blockages in hoses and booms. This gauge features a digital display in PSI, Bars or kPa. Uses industry standard quick connects. Operates with a simple one button operation. Shock proof rubber covering protects against drops. LCD shows range & Units: 3.0 - 160.0 PSI, 0.20 - 11.00 Bars, 20 - 1100 kPa. Accuracy: +/- 2% or +/- 1 PSI. Includes battery.

- Check nozzle pressure between the nozzle and nozzle body
- Verify Accuracy of Sprayer Pressure Sensor or Gauge
- Simple one button operation
- Simple One Button Operation
- Verify accuracy of sprayer pressure sensor or gauge
- Digital Display: 0.5 PSI, 0.05 BAR, 5 kPa
- Find blockages in hoses and booms
- Shock Proof Rubber Covering
- Accuracy: Greater of +/-1% of reading or +/-0.5 PSI, +/-0.5 Bars, or +/-5 kPa
- Uses Industry Standard Quick Connects
- Uses industry standard quick connects
- Find Blockages in Hoses and Booms
- Shock proof rubber covering protects against drops
- Installs Between Nozzle and Nozzle Body
- Display resolution: 0.5 PSI, 0.05 Bars, 5 kPa
- Includes Battery
- Includes 5 year battery
- Range: 3.0 - 160.0 PSI, 0.20 - 11.00 BAR, 20 - 1100 kPa

R&R Products Inc

3334 E Milber St Tucson, 85714

800-528-3446

<https://www.rrproducts.com/>



Spoton Spray Tip Pressure Tester

RSC28040



Specifications

Manufacturer	SpotOn
Pressure Range	10-160.0 PSI, 0.20-11.00 Bars, 20-1100 kPa