



# Alloy Machined Side-Eject Tine - .625MT x 6.000L x .540OD R365889



## Details

Alloy Machined Side-Eject tines remove a soil core which quickly exits the side of the tine through a precision machined slot. This slot is designed to avoid "plugging" that can occur using hollow tubular tines (especially the smaller diameters) in heavy soil conditions. R&R manufactures a wide selection of these side-eject tines machined from special high-carbon alloy steel solid bar and heat treated to RC45-48 in our own heat treatment facility. Very popular for the multiple tine holders which fit all greens aerators.

## Replaces

Jacobsen	339104
R&R Products	R3000446, R339104

## Specifications

Manufacturer	R&R Products
A - Tine Type	Alloy Machined Side-Eject
B - Tine Mounting Dia.	.625 in (15.9mm)
C - Tine Length	6 in (152mm)
D - Tine Tip Outside (Hole) Dia.	.540 in (13.7mm)
E - Tine Tip Inside (Core) Dia.	.400 in (10.2mm)
F - Tine Wall Thickness	.062 in (1.6mm)

## Fits Models

Jacobsen Aero King PT2448  
Jacobsen Aero King T1224

## R&R Products Inc

3334 E Milber St Tucson, 85714  
800-528-3446

<https://www.rrproducts.com/>



**Alloy Machined Side-Eject Tine - .625MT  
x 6.000L x .540OD  
R365889**



Jacobsen Verator VA-24

**R&R Products Inc**

3334 E Milber St Tucson, 85714

800-528-3446

<https://www.rrproducts.com/>